

RECEIVED
CENTRAL FAX CENTER**MAR 17 2010****CASE NO.: YOR020030362US1****Serial No.: 10/718,642****January 14, 2010****Page 2****PATENT****Filed: November 24, 2003**

1. (previously presented) A portable computing device comprising:

a display; and

a touch-sensitive display which is secondary and attachable to the display,

wherein said display and said touch-sensitive display present two adjoining display portions of a single display output at a first time and only the display but not the touch-sensitive display present the two adjoining display portions of the single display output at a second time.
2. (Previously Presented) The portable computing device of claim 1, wherein the touch-sensitive display is rotatably attachable to the display.
3. (Canceled).
4. (Previously Presented) The portable computing device of claim 1, wherein said touch-sensitive display displays a user-interface that overlays a portion of said single display output.
5. (Previously Presented) The portable computing device of claim 4, wherein the user-interface comprises a pointing device.
6. (Previously Presented) The portable computing device of claim 4, wherein the user-interface is reconfigurable in accordance with an instruction from a software application being executed on the portable computing device.

1201-SIAM1

RECEIVED
CENTRAL FAX CENTER

MAR 17 2010

CASE NO.: YOR020030362US1
Serial No.: 10/718,642
January 14, 2010
Page 3

PATENT
Filed: November 24, 2003

7. (Canceled)

8. (currently amended) A method of driving a portable computing device having a display attachable to a touch-sensitive display that is secondary and attachable to the display, the method comprising:

displaying a first of two adjoining display portions of a single display output in one of said display and said touch-sensitive display;

displaying a second of said two adjoining display portions of said single display output in the other of said display and said touch-sensitive display;

wherein said display and said touch sensitive display display said two adjoining display portions as a single display output, and

wherein the single display output is selected from the group of outputs including ~~consisting~~ of: a map, a computer drawing, a spreadsheet.

9. (Previously Presented) The method of claim 8, wherein the display is rotatably attachable to the touch-sensitive display.

10. (Previously Presented) The method of claim 8, wherein said touch-sensitive display further

1201-81AM1

CASE NO.: YOR020030362US1**Serial No.: 10/718,642****January 14, 2010****Page 4****PATENT****Filed: November 24, 2003**

comprises displaying a user-interface comprising a keyboard.

11. (Canceled).

12. (Previously Presented) The method of claim 10, further comprising reconfiguring the user-interface in response to an application state.

13. (Previously Presented) The method of claim 12, wherein reconfiguring the user-interface comprises reconfiguring the user-interface in response to a user preference.

14. (Previously Presented) The method of claim 12, wherein reconfiguring the user-interface comprises reconfiguring the user-interface in response to a user instruction.

15. (Canceled).

16. (Previously Presented) The method of claim 8, further comprising displaying a hot key that triggers the execution of a plurality of instructions in accordance with a state of the portable computing device.

17. (Original) The method of claim 8, further comprising displaying an application result.

18. (Previously Presented) The method of claim 17, wherein displaying an application result comprises displaying a first page of an electronic book on one of the display and the touch-sensitive display.

I201-81AM1

CASE NO.: YOR020030362US1
Serial No.: 10/718,642
January 14, 2010
Page 5

PATENT
Filed: November 24, 2003

19. (Previously Presented) The method of claim 18, wherein the displaying of the application result further comprises displaying a second page of an electronic book on the other one of the display and the touch-sensitive display.
20. (Previously Presented) The method of claim 8, further comprising displaying a drop-down menu on the touch-sensitive display.
21. (Previously Presented) The method of claim 10, wherein displaying the user-interface comprises displaying a color-coded keyboard.
- 22-34 (canceled).

1201-81AM1